



彩色 PE 絕緣積層被覆(CCP-LAP)市內電纜 (ML 1103-2)

線徑	對數	PE 絕緣體標準厚度	電纜芯徑(約)	積層被覆標準厚度(約)	圓型電纜		自持型電纜				標準長度		
					完成外徑(約)	概算重量	連接體寬與高	鍍鋅鋼絞線		完成外徑(約)	概算重量	圓型	自持型
								股數	被覆體厚度(約)				
mm	P	mm	mm	mm	mm	g/m	mm	mm	mm	mm	g/m	M	M
0.4	10	0.13	5.0	1.7	10.0	95	2×2	7/1.8	1.0	10.0×19.0	255	500	1,000
	20	"	7.0	"	11.0	120	"	"	"	11.0×20.0	295	"	"
	30	"	8.0	"	12.0	155	"	"	"	12.0×21.0	330	"	"
	50	"	10.0	"	14.0	230	"	"	"	14.0×24.0	405	"	500
	100	"	13.0	"	17.0	390	"	"	"	17.0×27.0	565	"	"
	200	0.13	19.0	"	23.0	705	2×2	7/2.0	1.0	23.0×33.0	915	500	500
	300	"	23.0	1.9	28.0	1,045	—	—	—	—	—	"	—
	400	"	27.0	2.0	32.0	1,375	—	—	—	—	—	"	—
	600	"	32.0	2.1	37.0	1,990	—	—	—	—	—	"	—
	0.5	10	0.15	6.0	1.7	10.0	100	2×2	7/1.8	1.0	10.0×20.0	275	500
20		"	8.0	"	12.0	160	"	"	"	12.0×22.0	335	"	"
30		"	9.0	"	14.0	210	"	"	"	14.0×23.0	385	"	"
50		"	12.0	"	16.0	315	"	"	"	16.0×25.0	490	"	500
100		"	17.0	"	21.0	515	"	7/2.0	"	21.0×31.0	725	"	"
200		0.15	22.0	1.8	27.0	1,025	3×3	7/2.3	1.2	27.0×38.0	1,315	500	500
300		"	28.0	2.0	33.0	1,545	—	—	—	—	—	"	—
400		"	33.0	2.1	37.0	2,020	—	—	—	—	—	"	—
600		"	40.0	2.3	45.0	2,975	—	—	—	—	—	"	—
0.65		10	0.20	7.0	1.7	12.0	150	2×2	7/1.8	1.0	12.0×22.0	330	500
	20	"	11.0	"	15.0	240	"	"	"	15.0×25.0	420	"	"
	30	"	13.0	"	17.0	340	"	"	"	17.0×27.0	520	"	"
	50	"	15.0	"	20.5	510	"	7/2.0	"	20.5×31.0	720	"	500
	100	"	21.0	1.8	27.0	930	3×3	7/2.3	1.2	27.0×38.5	1,220	"	"
	200	0.20	29.0	2.0	36.0	1,740	—	—	—	—	—	500	—
	300	"	36.0	2.2	41.0	2,600	—	—	—	—	—	345	—
	400	"	42.0	2.3	50.0	3,350	—	—	—	—	—	"	—
	600	"	50.0	2.6	56.0	4,950	—	—	—	—	—	"	—
	0.9	10	0.27	10.0	1.7	15.0	240	2×2	7/1.8	1.0	15.0×24.0	420	500
20		"	14.0	"	18.0	390	"	"	"	18.0×28.0	600	"	"
30		"	17.0	"	22.5	580	"	7/2.0	"	22.5×33.0	790	"	"
50		"	21.0	1.8	27.0	900	3×3	7/2.3	1.2	27.0×38.5	1,185	"	"
100		"	30.0	2.0	36.0	1,670	—	—	—	—	—	"	—