



發泡、充實 PE 雙重絕緣充膠積層被覆(FS-JF-LAP)市內電纜(ML1102-3)

線徑	對數	F.S 雙重絕緣標準厚度	電纜芯徑(約)	積層被覆厚度	完成外徑(約)	概算重量	標準長度
mm	P	mm	mm	mm	mm	Kg/m	M
0.4	10	0.13	5.5	1.7	9.0	0.09	500
	20	"	7.0	"	11.0	0.13	"
	30	"	8.5	"	12.0	0.18	"
	50	"	10.0	"	14.0	0.25	"
	100	"	14.0	"	18.0	0.44	"
	200	0.13	20.0	1.7	24.0	0.80	500
	300	"	24.0	1.9	28.0	1.15	"
	400	"	28.0	2.0	33.0	1.60	"
0.5	10	0.15	6.5	1.7	10.0	0.11	500
	20	"	8.0	"	12.0	0.18	"
	30	"	10.0	"	14.0	0.24	"
	50	"	12.0	"	16.0	0.35	"
	100	"	17.0	"	21.0	0.63	"
	200	0.15	23.0	1.8	27.0	1.16	500
	300	"	29.0	2.0	34.0	1.67	"
	400	"	33.0	2.2	39.0	2.30	"
0.65	10	0.20	8.0	1.7	12.0	0.16	500
	20	"	11.0	"	15.0	0.28	"
	30	"	13.0	"	17.0	0.36	"
	50	"	16.0	"	20.0	0.54	"
	100	"	23.0	1.8	27.0	1.00	"
	200	0.20	31.0	2.0	36.0	1.85	500
	300	"	37.0	2.2	42.0	2.76	"
	400	"	42.0	2.3	48.0	3.80	"
600	"	51.0	2.6	57.0	5.40	345	