



發泡、充實PE 雙層絕緣鋁帶鋼帶PE 被覆(FS-STP)市內電纜 (ML 1021-2)

線徑	公稱對數	F.S 雙層 絕緣體 標準 厚度	電纜 芯徑 (約)	縱放 止水 不織 布帶 寬度 (約)	聚乙 烯 被 覆 體 標 準 厚 度	無鎧裝電纜		鋼帶鎧裝電纜		標準 長度
						外徑 (約)	概算 重量	外徑 (約)	概算 重量	
mm	P	mm	mm	mm	mm	mm	kg/m	mm	Kg/m	M
0.4	400	0.11	26.0	25	1.5	32.0	1.57	42.0	3.09	500
	600	"	31.0	30	1.6	38.0	2.20	47.0	3.95	"
	800	"	35.0	"	1.8	42.0	2.81	55.0	5.32	250
	1,000	"	40.0	35	1.9	48.0	3.40	60.0	6.17	"
	1,200	"	43.0	"	2.0	51.0	4.08	64.0	7.07	"
	1,400	0.11	47.0	40	2.1	55.0	4.69	67.0	7.87	250
	1,600	"	50.0	"	2.2	58.0	5.29	71.0	8.64	"
	1,800	"	52.0	"	2.3	61.0	5.88	73.0	9.36	"
	2,000	"	54.0	"	2.4	63.0	6.47	75.0	10.07	"
	2,200	"	57.0	"	2.5	66.0	7.06	78.0	10.80	"
	2,400	0.11	59.0	40	2.5	68.0	7.56	80.0	11.50	250
	2,600	"	61.0	"	2.6	70.0	8.24	82.0	12.15	"
	2,800	"	64.0	45	2.7	73.0	8.83	86.0	12.96	"
	3,000	"	66.0	"	2.8	76.0	9.45	88.0	13.70	"
3,200	"	68.0	"	3.0	78.0	10.06	90.0	14.43	"	
0.5	400	0.13	31.0	25	1.6	38.0	2.21	48.0	3.96	500
	600	"	38.0	35	1.8	45.0	3.14	57.0	5.77	250
	800	"	42.0	"	1.9	50.0	4.05	62.0	6.94	"
	1,000	"	48.0	40	2.1	56.0	4.97	68.0	8.19	"
	1,200	"	53.0	"	2.3	61.0	5.96	73.0	9.46	"
	1,400	0.13	57.0	40	2.5	66.0	6.88	78.0	10.60	250
	1,600	"	60.0	"	2.5	70.0	7.75	82.0	11.68	"
	1,800	"	63.0	"	2.6	72.0	8.63	85.0	12.72	"
	2,000	"	66.0	45	2.8	76.0	9.54	88.0	13.79	"
	2,200	"	69.0	"	3.0	79.0	10.45	91.0	14.89	"
2,400	"	72.0	"	3.0	82.0	11.31	94.0	15.86	"	
0.65	400	0.15	38.0	35	1.8	45.0	3.42	58.0	6.09	250
	600	"	47.0	40	2.1	55.0	4.97	67.0	8.16	"
	800	"	53.0	"	2.3	61.0	6.45	73.0	9.97	"
	1,000	"	59.0	"	2.5	68.0	7.95	80.0	11.83	"
	1,200	"	65.0	45	2.8	74.0	9.47	86.0	13.64	"
	1,400	"	70.0	"	3.0	80.0	10.96	92.0	15.50	"
0.9	400	0.21	52.0	40	2.3	61.0	6.19	73.0	9.68	250