



UL 2468 UL 2555 FLAT RIBBON CABLE 80°C 300V 排線

Conductor: 導體

- Fully annealed tinned copper per ASTM B-33.
全部為鍍錫軟銅線依照 ASTM B-33 規範
- 26 thru 20 AWG

Insulation: 絕緣體

- Premium grade color coded PVC
特製彩色 PVC
- Temperature Rating: 80°C
耐溫等級：80°C
- Voltage Rating: 300 Volts
電壓等級：300 Volts

Applications: 應用

- Internal wiring of electrical and electronic equipment.
電氣迴路內部配線及儀表用線

Industry Approvals: 產品認證

- UL Style 2468, 2555 File No. E117873.
- CSA AWM File NO. LL82009.
- Passes UL VW-1 Vertical Flame Test.
OSHA acceptable

Color: 絕緣體顏色

- Available with red, yellow, blue, white, black, green, brown, orange, purple, gray and pink.
紅、黃、藍、白、黑、綠、棕、橙、紫、灰、粉紅等，可依客戶要求配色

Packaging: 包裝

- 1,000 ft (305m)
1,000 呎(305 米)
- Available on coils or reels
可用卷裝或軸裝

UL Style & CSA Type 型號	AWG 線規尺寸	Conductor Composition 導體組成	No. of Cores 芯線數目	Insulation Thickness 絕緣厚度	Nominal O.D. 完成外徑
		No./mm		mm	mm
UL 2468 CSA AWM	26	7/0.160	2	0.45	1.4x 2.8
			3	"	1.4x 4.2
			4	"	1.4x 5.6
			5	"	1.4x 7.0
			6	"	1.4x 8.4
			7	"	1.4x 9.8
			24	7/0.203	2
	3	"			1.5x 4.5
	4	"			1.5x 6.0
	5	"			1.5x 7.5
	6	"			1.5x 9.0
	7	"			1.5x 10.5
	22	7/0.254			2
			3	"	1.7x 5.1
			4	"	1.7x 6.8
			5	"	1.7x 8.5
			6	"	1.7x 10.2
			7	"	1.7x 11.9
			20	7/0.320	2
	3	"			1.9x 5.7
	4	"			1.9x 7.6
	5	"			1.9x 9.5
	6	"			1.9x 11.4
	7	"			1.9x 13.3

ASTM American Society of Testing and Material.

VW-1 Pass a vertical flame test.

OSHA Occupational Safety and Health Administration

美國材料試驗協會

垂直耐燃試驗合格

職業安全及衛生管理局