



UL SPT FLEXIBLE CORD 60/105°C 300V 平型電源線

Conductor: 導體

- Fully annealed stranded bare copper per ASTM B-33.
全部為軟銅絞線依照 ASTM B-33 規範
- 18 thru 10 AWG

Insulation: 絕緣體

- Premium grade color coded PVC
特製彩色 PVC
- Temperature Rating: 60°C or 105°C
耐溫等級: 60°C 或 105°C
- Voltage Rating: 300 Volts
電壓等級: 300 Volts

Applications: 應用

- SPT-1 & SPT-2: For use in household clocks, fans, radios and similar appliances
家用掛鐘、電扇、收音機及其他家用電氣用品
- UL 20288: Use in lighting fixtures.
燈具用線

Color: 絕緣體顏色

- Available with yellow, white, black, brown, gray and gold.
黃、白、黑、棕、灰及金黃色等，可依客戶要求配色

Packaging: 包裝

- 1,000 ft (305m) per coil
1,000 呎(305 米)
- Other put-ups available.
其他包裝方式依客戶之需求

Industry Approvals: 產品認證

- UL SPT File No.E117872.
- CSA SPT File NO. LL82009.
- Passes UL VW-1 Vertical Flame Test.OSHA acceptable

UL Style & CSA Type 型號	AWG 線規 尺寸	Conductor Composition 導體組成	No.Of Cores 芯線數目	Insulation Thickness 絕緣厚度	Nominal O.D. 完成外徑
		No./mm		mm	mm
SPT-1	18	41/0.160	2	0.76	2.7x 5.4
	18	41/0.160	3	"	2.7x 7.9
SPT-2	18	41/0.160	2	1.14	3.5x 7.0
	16	65/0.160		"	3.8x 7.6
	18	41/0.160	3	1.14	3.5x 8.6
	16	65/0.160		"	3.8x 9.6
SPT-3	18	41/0.160	2	1.52	4.4x 8.7
	16	65/0.160		"	4.8x 9.5
	14	41/0.254		2.03	6.0x 12.0
	12	65/0.254		2.41	7.4x 14.0
	10	104/0.254		2.79	9.1x 18.2
	18	41/0.160	3	1.52	4.4x 10.7
	16	65/0.160		"	4.8x 11.8
	14	41/0.254		2.03	6.0x 14.5
	12	65/0.254		2.41	7.4x 16.5
	10	104/0.254		2.79	9.1x 18.8
UL 20288	18	41/0.160	2	1.02	3.3x 5.8

ASTM American Society of Testing and Material.

VW-1 Pass a vertical flame test.

OSHA Occupational Safety and Health Administration

Transparent PVC Used in UL 20288

美國材料試驗協會

垂直耐燃試驗合格

職業安全及衛生管理局

透明 PVC 絕緣適用於 UL 20288