



聚乙烯絕緣聚氯乙烯被覆(PE-PVC)屋內電纜

(ML 3030-1)

導體直徑	對數	PE絕緣體標準厚度	電纜芯徑(約)	PVC被覆體標準厚度	完成外徑(約)	概算重量	標準單長
mm	P	mm	mm	mm	mm	Kg/Km	M
0.4	6	0.13	4.0	1.3	7.0	52	500
	10	"	5.0	"	8.0	69	"
	20	"	6.0	"	9.0	109	"
	30	"	7.0	"	10.0	143	"
	50	"	10.0	1.4	13.0	218	"
	100	"	14.0	1.6	17.0	397	"
	200	"	18.0	1.9	22.0	746	"
	300	"	23.0	2.0	27.0	1,076	"
	400	"	26.0	2.3	31.0	1,427	"
600	"	31.0	2.4	36.0	2,061	"	
0.5	6	0.15	5.0	1.3	8.0	67	500
	10	"	6.0	"	9.0	90	"
	20	"	7.0	"	10.0	146	"
	30	"	9.0	"	12.0	198	"
	50	"	12.0	1.4	15.0	309	"
	100	"	16.0	1.6	20.0	565	"
	200	"	22.0	2.0	26.0	1,087	"
	300	"	27.0	2.1	31.0	1,577	"
	400	"	31.0	2.4	36.0	2,092	"
600	"	38.0	2.5	43.0	3,044	"	