



硬銅/軟銅絞線 (英國標準 BS 6360 class 2)

標稱 截面積	構成	絞合外徑	最大直流電阻 20°C (Ω / km)		重量
			單芯	多芯	
mm ²	No./mm	mm			kg/km
1.0	7/0.40	1.20	17.7	18.1	8.0
1.5	7/0.53	1.59	11.9	12.1	12.5
2.5	7/0.67	2.01	7.27	7.41	22.4
4	7/0.85	2.55	4.52	4.61	36.1
6	7/1.04	3.12	3.02	3.08	54.0
10	7/1.35	4.05	1.79	1.83	90.8
16	7/1.70	5.10	1.13	1.15	145.0
25	7/2.14	6.42	0.712	0.727	229.0
35	7/2.52	7.56	0.507	0.518	317.0
50	19/1.78	8.90	0.379	0.387	429.0
70	19/2.14	10.70	0.262	0.268	620.0
95	19/2.52	12.60	0.189	0.193	860.0
120	37/2.03	14.21	0.150	0.153	1,086.0
150	37/2.25	15.75	0.122	0.124	1,334.0
185	37/2.52	17.64	0.0972	0.0991	1,673.0
240	61/2.25	20.25	0.0740	0.0754	2,199.0
300	61/2.52	22.68	0.0590	0.0601	2,759.0
400	61/2.85	25.65	0.0461	0.0470	3,528.0
500	61/3.20	28.80	0.0358	0.0366	3,610.0

註：導體若為硬銅線，其最大直流電阻為表列直除以 0.97 即可。